SpeedShare

Key features

- Compact high speed ADSL modem with USB connection
- Connect your desktop or notebook PC to your ADSL internet connection instantly via USB
- Easy modem configuration thanks to user friendly installation wizard
- Suitable for USB 2.0 and USB 1.1; Powered by USB (no power adapter required)
- Share your ADSL connection with other computers (requires a LAN connection)

14359 - USB ADSL Modem MD-3100

With over 20 years of experience as the only independent manufacturer of affordable technological quality computer peripherals, Trust offers a complete and innovative assortment of 250 products. Each product is carefully developed with the focus on functionality and users comfort; in this process price in proportion to quality is of importance. The assortment is divided into four marketing concepts namely Portable Solutions, Bluetooth Solutions, Internet Telephony Solutions and MP3 Solutions and into twelve sub brands. This classifies the complete assortment in orderly product groups.

Trust International B.V. (www.trust.com) is active in 30 European countries. The product range is available through all the national and European wide retailers and resellers. More than 230 employees are working at the offices in the Netherlands, Germany, France, Spain, Italy, United Kingdom, Poland, Portugal, Czech Republic, Hungary, Austria and Switzerland. Trust offers complete services to both its partners and consumers.

Technical Specifications

- Annex A (A)DSL modem for an analogue (POTS) line
- USB 1.1 connection to PC
- RJ11 (A)DSL Annex A connection for analogue (POTS) line
- Compatible with all ADSL Internet providers
- Windows plug and play
- (A)DSL standards compliant
- Up to 8 Mbps downstream speed (depends on ISP contract)
- Up to 1 Mbps upstream speed (depends on ISP contract)
- Indications for power, (A)DSL Link
- Line specifications:
- ITU auto mode (G.dmt or G.lite)
- G.922.1 (G.dmt)
- G.922.2 (G.Lite)
- ANSI T1.413 i2
- Protocols support:
- RFC 1483; Bridged IP over ATM
- RFC 2364; PPP over ATM (PPPoA)
- RFC 2516; PPP over Ethernet (PPPoE)
- RFC 1577 (Classical Internet Protocol over ATM)
- ATM AAL5 (Adaption Layer type 5)
- Encapsulation support:
- LLC
- VC-MUX
- VPI and VCI Settings
- VPI Value from 0 to 255
- VCI Value from 32 to 65535

More Information

- Item number: 14359
- Product link: www.trust.com/14359

TRUST.COM